

ELITER

MOBILE ANTENNAS

☑ Designed for mounting from inside or outside of a vehicle body.

Electrical Data	ELITER3902
Frequency	380 – 470 MHz
Nominal Gain	4 dBq (rel. $\lambda/4$ -wave)
Bandwidth VSWR <1,5:1	10 MHz
Radiation Pattern	Omni-directional
Polarisation	Vertical
Rated Power	50 W
Impedance	50 Ω
Termination	No connector
Coax Cable	6 m RG-58 (other lengths available on request)
Mechanical Data	
Max. wind velocity	220 km/h
Whip	Tapered, 17 – 7PH SS
Mounting Hole Size	12 mm
Adjustment	30° Bendable center pin
Colour	Black
Dims	OD 30 mm x 585 mm
Shipping Dims	0.4 kg / 59 x 11 x 3 cm

REPLACEMENT PARTS



ERBC
A10AA1662A

ELITER BASE & CABLE
1/4 & 5/8



EW3902
A11AA0535A


WHIP ASSY
ELITE 5/8



ELITER3902

A10AA1660A

UHF ELITER 5/8 WAVE
OPEN COIL



Horizontal Pattern

ISO 9001
CERTIFIED

www.webb.co.za
webb@webb.co.za

tel+27 11 719-0000
fax+27 11 444-2288

© 2017/05/11 ... Specifications subject to change without notice...