

ELITER

MOBILE ANTENNAS

- ☑ Designed for mounting from inside or outside of a vehicle body.

Electrical Data	ELITER3900
Frequency	380 – 470 MHz
Nominal Gain	Unity
Bandwidth VSWR <1,5:1	10 MHz
Radiation Pattern	Omni-directional
Polarisation	Vertical
Rated Power	50 W
Impedance	50 Ω
Termination	No connector
Coax Cable	6 m RG-58 (other lengths available on request)

Mechanical Data

Max. wind velocity	220 km/h
Whip	Tapered, 17 – 7PH SS
Mounting Hole Size	12 mm
Adjustment	30° Bendable center pin
Colour	Black
Dims	OD 30 mm x 170 mm
Shipping Dims	0.36 kg / 24 x 11 x 3 cm



REPLACEMENT PARTS



ERBC
A10AA1662A

ELITER BASE & CABLE
1/4 & 5/8




EW3900
A11AA0530A

ELITE 1/4
WHIP

ELITER3900

A10AA1659A

UHF ELITE-R 1/4 WAVE



Horizontal Pattern

**ISO 9001
CERTIFIED**

www.webb.co.za
webb@webb.co.za

tel+27 11 719-0000
fax+27 11 444-2288

© 2017/05/11 ... Specifications subject to change without notice...