



MOBILE ANTENNAS

- ☑ The ELITE130 is a base loaded, 5/8 wavelength mobile antenna designed for mounting from the inside or outside of the vehicle body.
- ☑ Antennas supplied with 4 m RG-58 coaxial cable as standard, other lengths available on request.

Electrical Data	ELITE130
Frequency	132...174 MHz
Nominal Gain	2 dBq (rel. $\lambda/4$ -wave)
Bandwidth VSWR <1,5:1	3 MHz
VSWR	< 1,5:1
Radiation Pattern	Omni-directional
Polarisation	Vertical
Rated Power	100 W
Impedance	50 Ω
Termination	4 m RG-58, no connector

Mechanical Data

Max. wind velocity	220 km/h
Whip	Tapered 17 – 7PH SS
Mounting Hole Size	12 mm
Adjustment	30° Bendable center pin
Colour	Black
Dims	1540 mm
Shipping Dims	0.3 kg / 155 x 11 x 5 cm



REPLACEMENT PARTS



EBC

A10AA0131A 4 m RG-58 /

A10AA0979A 6 m RG-58

Base & cable complete




EW130

A10AA0183A

ELITE130

A10AA0586A

ENCAPSULATED BASE
LOADED 5/8



Horizontal Pattern

**ISO 9001
CERTIFIED**

www.webb.co.za
webb@webb.co.za

tel+27 11 719-0000
fax+27 11 444-2288

© 2017/05/11 ... Specifications subject to change without notice...

JASCO
INSPIRE. INNOVATE.